

Stahl Industrial Parts Catalog

Axiparts Global Industrial RFQ Platform

Email: info@axiparts.com

Website: <https://axiparts.com>

Premium RFQ catalog for Stahl industrial spare parts, MRO components and replacement products. Every listed product is linked directly to its live RFQ product page.

Brand: Stahl

Listed Products in This PDF: 202

Catalog URL: <https://axiparts.com/catalogs/brands/stahl.pdf>

Part Number	Product Description	Live RFQ Link
01644E0G	01644E0G 8003 PTB 01 ATEX 1129U basmal■ buton	Open Product RFQ Page
019116	019116 HOLDER,LAMP,PIN,240VAC,40W Material Contact : STANDARD Power Rated : 40 W Voltage, Rated : 240 VAC Type, Lamp Cap : PIN Basic Data Text : RIGHT	Open Product RFQ Page
106073	106073 Cable Glands made of moulded plastic with strain relief explosion-protected Type : HSK-K-MZ-Ex Thread size : M16 x 1.5 Thread length : 15 mm Ma	Open Product RFQ Page
106074	106074 Cable Glands made of moulded plastic with strain relief explosion-protected Type : HSK-K-MZ-Ex Thread size : M20 x 1.5 Thread length : 15 mm Ma	Open Product RFQ Page
108951	108951 (2PIN fluorescent tupe 36 W diameter 26mm CCT No.: 85393110 DE Net weighth: 0,200 KG)	Open Product RFQ Page
108952	108952 (Zweistift-Leuchtstofflampe18 Watt Durchmesser 26mm)	Open Product RFQ Page
109133	109133 (Natriumdampf-Hochdrucklampe 400W,Röhrenform)	Open Product RFQ Page
114779	114779 6000/521-8011-3130 Lighting with 2-pin 1x18/20W Light Fittings for Fluorescent Lamps Series EXLUX 6000, explosion protected Lamps Number of lam	Open Product RFQ Page
114847	114847 6000/522-9011-0130 Light fitting with 2pin 18/20W	Open Product RFQ Page
115738	115738 (Klimastutzen M25)	Open Product RFQ Page
115806	115806 (Through wiring DV5 20W accessorie)	Open Product RFQ Page
115819	115819 (Through wiring DV5 65W accessorie)	Open Product RFQ Page
115828	115828 (Einschubplatte 2xM25x1,5 Zubeh)	Open Product RFQ Page
117252	117252 (6041/42 Lamp socket G13 spare part)	Open Product RFQ Page
117590	117590 Reparatursatz 36W Elektronisches Vorschaltgerät + Zubehör	Open Product RFQ Page
119173	119173 6108/1081-8017-74-00 Compact emergency light fitting 1x8W	Open Product RFQ Page
119829	119829 Auxiliary lens, clear	Open Product RFQ Page
119844	119844 Lead-gel Battery with fuse;4 V;3.5 Ah	Open Product RFQ Page

Part Number	Product Description	Live RFQ Link
119848	119848 Main lamp(halogen lamp), 4.0 V;2 W; packing unit 2 pc's	Open Product RFQ Page
119849	119849 Economy lamp 3.7 V; 1.1 W; packing unit 10 pc's	Open Product RFQ Page
120431	120431 / 6147/2-2 (Hand lamp explosion-protected Type : 6147/2-2 Enclosure material : Light metal Protective glass material : Temperature-resistant pr	Open Product RFQ Page
121700	121700 6388/1-2-2 Bulkhead light fitting Bulkhead Light Fitting Series 6388, explosion protected Lamps: up to 150 W Colour of glass: clear For use in:	Open Product RFQ Page
123291	123291 6508/1081-8017-74-00 Compact emergency light fitting 1x8W	Open Product RFQ Page
124632	124632 6600/522-8010-2230 Obsolete!! Replaced by 6401 (Leuchte für Leuchtstofflampen explosionsgeschützt,Anzahl der Leuchtmittel:2, Lampenleistung:18	Open Product RFQ Page
124633:	124633: 6600/521-8510-2150 (Leuchte für Leuchtstofflampen,Typ: 6600/52.-.....,Technische Daten: Gas-Explosionsschutz: II 3 G EEx nA II T4 Staub -	Open Product RFQ Page
124643	124643 6600/542-8010-2230 (Leuchte für Leuchtstofflampen explosionsgeschützt, Anzahl der Leuchtmittel: 2, Lampenleistung: 36 W)	Open Product RFQ Page
124894	124894 (MontageschieneZubehoer)	Open Product RFQ Page
124910	124910 (WandbefestigungswinkelZubehoer)	Open Product RFQ Page
127244	127244 8003/131-008-2-r-MS1 Schlüsselschalter S-S Käfigzugfederklemme Befehlstaster / Schalter für Schalttafeleinbau Reihe 8003, explosionsgeschützt A	Open Product RFQ Page
(129095)	(129095) 8013/311-AL LED Indicating Lamp for panel mounting	Open Product RFQ Page
130171	130171 8030/51-033 Installation switch, 2-pol, ON-OFF Installationsschalter Reihe 8030/51, explosion protected Version: OFF switch Number of poles: 2-	Open Product RFQ Page
130176	130176 8030/51-035 Installationsschalter 2-polig Wechselschalter, Bemessungsbetriebsspannung: bis 250 V DC / 690 V AC	Open Product RFQ Page
130679	130679 Control device system Series ConSig 8040 explosion-protected Type : 8040/1180X-10L07BA05 Rated operational voltage AC : 550 V Rated operational	Open Product RFQ Page
130692	130692 8040/1280X-01L13BA05-01L08BA05 Befehls-/Meldegerät	Open Product RFQ Page
130899	130899 8040/1280X-01L13BA02-01L08BA01 Befehls-/Meldegerät pushbutton	Open Product RFQ Page
132530	132530 (8080/1-2 NO/NC Contact element SPARE PART snap-action contact with spring entspricht Ihrer Teile-Nr. 132528)	Open Product RFQ Page
132636	132636 8082/1-1-00 Oeffner Kontaktelement Schraubklemme Befehlstaster Reihe 8082, explosionsgeschützt Anschluss: Schraubklemmen Kontaktbestückung: 1 Ö	Open Product RFQ Page

Part Number	Product Description	Live RFQ Link
132640	132640 8082/1-2-00 Schliesser Kontaktelement Schraubklemme Befehlstaster Reihe 8082, explosionsgeschützt Anschluss: Schraubklemmen Kontaktbestückung:	Open Product RFQ Page
132973	132973 8102/21-32-C995 Junction Box	Open Product RFQ Page
133128	133128 8118/122-199 Terminal box Ex e	Open Product RFQ Page
136126	136126 8146/5052-C796 Alarm- und Feuermelder mit Pilzsperrtaster	Open Product RFQ Page
136678	136678 8146/5041 CONTROL STATION - Hazard Certificate : Y, Hazard Classification : EEX ED IIC T6, Hazard Classification : EEX II 2G, Hazard Classificat	Open Product RFQ Page
136703	136703 Control stationType : 8146/5061Technical data:Gas - Explosion protection: Ex II 2 G Ex de IIC T6 GbDust - Explosion protection: Ex II 2 D Ex tb	Open Product RFQ Page
138382	138382 Blanking Plug	Open Product RFQ Page
138383	138383 (nut M16 brass nickel plated 50pcs Locknut, metric brass, nickel plated Internal thread d: M16 x 1.5 Width across flats [mm]: 19 Packing unit:	Open Product RFQ Page
138389	138389 nut M20x1.5	Open Product RFQ Page
138394	138394 Blanking Plug	Open Product RFQ Page
138395	138395 (nut M25 brass nickel plated 50pcs Locknut, metric brass, nickel plated Internal thread d: M25 x 1.5 Width across flats [mm]: 29 Packing unit:	Open Product RFQ Page
138406	138406 (blanking plugs f. cable glands Pg9 /M16.....50pcs CCT No.: 39269097 DE Net weigth: 0,061 KG)	Open Product RFQ Page
138417	138417 (blanking plugs f. multiple cable glands, d 5,5mm...50pcs CCT No.: 39269097 DE Net weigth: 0,031 KG)	Open Product RFQ Page
138454	138454 8161/5-M20-13 Cable gland Ex e polyamide, 6-13mm, 50 pcs Cable Glands Series 8161, explosion protected Version: 8161/5 Ex e (black) Thread size	Open Product RFQ Page
138482	138482 8161/5-M16-9 Cable gland Ex e polyamide, 4-9mm, 50 pcs Cable Glands Series 8161, explosion protected Version: 8161/5 Ex e (black) Thread size:	Open Product RFQ Page
138520	138520 8161/5-M25-17 (Cable Glands explosion-protected Type : 8161/5-M25-17 Thread size : M25 Thread length : 10 mm Material : Polyamide Colour : blac	Open Product RFQ Page
143544	143544 8290/3-M25 (Stopping Plug explosion-protected Type : 8290/3-M25 Material : Polyamide Thread size : M25 Drive : Hexagon socket Application range	Open Product RFQ Page
143556	143556 8290/3-M16 (Stopping Plug explosion-protected Type : 8290/3-M16 Material : Polyamide Thread size : M16 Drive : Hexagon socket Application range	Open Product RFQ Page
145280	145280 8491/11-230 Hupe mit Horn 230V, AC	Open Product RFQ Page
145285	145285 8491/21-230 Flachhupe 230V, AC	Open Product RFQ Page

Part Number	Product Description	Live RFQ Link
150578	150578 Switch socket	Open Product RFQ Page
150579	150579 8570/12-306 Plug 2P+PE 16A 200-250V, 60+60Hz, 6h, blue	Open Product RFQ Page
153029	153029 (Type 8579/12-406) Plug explosion-protected	Open Product RFQ Page
155399	155399 (Push button explosion-protected Type : 8602A0001-1 Enclosure material : Polyamide Seal : Standard Mounting : with threaded Application range (Open Product RFQ Page
155476	155476 (Rotary handle, large, raised explosion-protected Type : 8602A0724-1-ss-0 Enclosure material : Polyamide Seal : Silicone Mounting : with thread	Open Product RFQ Page
155785	155785 (Label I O II)	Open Product RFQ Page
155908	155908 labels buttons series 8003	Open Product RFQ Page
160321	160321 9170/10-12-21S IS PAC Isolating Repeater Switching Repeater Field Circuit Ex i explosion-protected Type : 9170/10-12-21s Max. Voltage Uo : 10,6	Open Product RFQ Page
167080:	167080: 6608/522-9611-7267 (Notlicht-Langfeldleuchte für Leuchtstofflampen Typ: 6608/5.2-9...-...7 Technische Daten: Gas-Explosionsschutz: II 3 G EEx	Open Product RFQ Page
168554	168554 Reparatursatz 2x36W QTP8 Ers.QTIS-B Elektronisches Vorschaltgerät + Zubehör	Open Product RFQ Page
168555	168555 Reparatursatz 2x18W QTP8 Ers. QTISElektronisches Vorschaltgerät + Zubehör	Open Product RFQ Page
1739084219	1739084219 Control Pendant selection STH 6102-009	Open Product RFQ Page
201386	201386 8579/31-506 Switch socket 3P+N+PE 63A, 200/346-240/415V, 50+60Hz, red CCT No.: 85366990 DE Net weighth: 7,800 KG	Open Product RFQ Page
201389	201389 (TYPE : 8579/31-406) Switch socket explosion-protected	Open Product RFQ Page
201404	201404 8146/5-V37-302-50-0050 SPARE OF TYPE : 8537/2-302-7000; 8537/2-702-7000 (Safety Switches 16 A explosion-protected Rated operational voltage AC	Open Product RFQ Page
203478	203478 6141/61-16 Hand lamp with LED Hand Lamp Series 6141/6, explosion protected Rated data: 3 V Batteries: Hand lamps are supplied with batteries. F	Open Product RFQ Page
203970	203970 Fibre optic top piece for 6141/61-16	Open Product RFQ Page
204142	204142 Accessories Belt case for handlamp 6141 Size 1	Open Product RFQ Page
205208	205208 Sounder, Yodalex,Audible Alarm	Open Product RFQ Page
205308	205308 Sounder Ex i ATEX	Open Product RFQ Page
205315	205315 Sounder Ex i ATEX, T6	Open Product RFQ Page
205336	205336 MCP/PB/SP/Ex/A+B+C+D/EU/R/LED/D/T Drucktaster-Handfeuermelder, 12-50VDC/	Open Product RFQ Page
211124	211124 Batterie 6148 6V 4,5Ah replacement set	Open Product RFQ Page

Part Number	Product Description	Live RFQ Link
212333	212333 Diffusing lens clear accessories	Open Product RFQ Page
224398	224398 8040/114-O2MN1-UL Befehls- und Meldegeraet	Open Product RFQ Page
6000	6000 802260 Original Spare Part	Open Product RFQ Page
6000/521-8011-3130	6000/521-8011-3130 FLORESAN TOP ARMATÜR EX PROOF FLUORESCENT LAMP FITTING SERIES EXLUX 6000(ZONE 1,2) 18/20W LAMPS,220V ELECTRONIC BALLATS 1 CABLE GLA	Open Product RFQ Page
6000/522-9011-0130	6000/522-9011-0130 18W EXPROOF	Open Product RFQ Page
6000/542-	6000/542- 9011-0130 / 114863 Light fitting for fluorescent lamps explosion -protected	Open Product RFQ Page
6000/542-9391-013	6000/542-9391-013 (2*36)	Open Product RFQ Page
6014	6014 VB Original Spare Part	Open Product RFQ Page
6041/42	6041/42 (Lampenfassung für Sockel G13Ersatz Bemessungsbetriebsspannung: bis 1000 V)	Open Product RFQ Page
6121/5312-640-01	6121/5312-640-01 / 119414 (Scheinwerfer Größe 3 unkompensiert Scheinwerfer Reihe 6121, explosionsgeschützt Ausführung: Baugröße 3, 6121/53. Lampenart	Open Product RFQ Page
6142	6142 main lamp, halogen lamp, 4.0 V; 2W, order number 119848	Open Product RFQ Page
6142/21	6142/21 Portable Lamp and Charging unit(12/24 V AC)	Open Product RFQ Page
6148/1111-111	6148/1111-111	Open Product RFQ Page
6149/2-5211-5010	6149/2-5211-5010 LED Inspektionsleuchte explosionsgeschützt	Open Product RFQ Page
6161/2-11-621-0	6161/2-11-621-0 Original Spare Part	Open Product RFQ Page
6401	6401	Open Product RFQ Page
6600/542-8011-2230	6600/542-8011-2230 (2X18) Original Spare Part	Open Product RFQ Page
669982	669982 Plug 16A,20-26V,2P,60HZ, FOR BALSCEENNORM	Open Product RFQ Page
80	80 130 03 21 0 - OBSOLETE (REPLACED BY 8013/311-AL) Green	Open Product RFQ Page
8003/111-009	8003/111-009 Mushroom stay-put button with key lock, NO/NC spring clamp terminal	Open Product RFQ Page
8003/111-010	8003/111-010 mushroom head stay-put pushbutton NC-NO cage clamp, no key lock	Open Product RFQ Page
8003/111-015	8003/111-015 (Control devices explosion-protected Rated operational voltage AC : 550 V Rated operational current : 6 A Number of switching positions :	Open Product RFQ Page
8003/131-001	8003/131-001 (Control devices explosion-protected Rated operational voltage AC : 550 V Rated operational current : 6 A Number of switching positions	Open Product RFQ Page
8010/2-01	8010/2-01	Open Product RFQ Page

Part Number	Product Description	Live RFQ Link
8013/22-02-43	8013/22-02-43 YELLOW SIGNAL LAMP 24 VDc, 1,5 W (Eex de IICT6)	Open Product RFQ Page
8013/22-02-93	8013/22-02-93 REPLACED BY 129095 8013/311-al WHITE SIGNAL LAMP 24 VDc , 1,5 W (Eex de IICT6)	Open Product RFQ Page
8013/321-AL	8013/321-AL (LED Indicating Lamp for panel mounting explosion-protected Rated operational voltage AC : 30 V Enclosure material : Polyamide Luminous co	Open Product RFQ Page
80400019	80400019 Fahrtrieb SY 13211313 für GW, 2 Stück 332825 s/n Fab.-Nr. 7510074	Open Product RFQ Page
8040/11	8040/11 Control Equipment	Open Product RFQ Page
8040/1180X-09XXXBA05	8040/1180X-09XXXBA05 - obsolete-replaced by 8040/1190X-09XXXBA05 Control device system Series ConSig 8040 explosion-protected	Open Product RFQ Page
8040/1180X-10L07BA08.	8040/1180X-10L07BA08. (Befehlsgerätesystem Reihe ConSig 8040 explosionsgeschützt Typ, Bemessungsbetriebsspannung AC : 550 V Bemessungsbetriebsstrom :	Open Product RFQ Page
8040/12	8040/12 Control Unit System Series 8040 Start-Stop-Potentiometer	Open Product RFQ Page
8040/1380X-	8040/1380X- 54CO6XXXX- 01L13BA05- 01L08BA05 EX-PROOF MOTOR KUMANDA KUTUSU ENÜST TARAFINDA KIRMIZI SİYAL İKİLİ ORTA KISIMDA YEŞİL START(1)BUTONU EN AL	Open Product RFQ Page
8040/2380Z-	8040/2380Z- 54C06XXXX- 31E...F.. Control Unit System Series 8040 LED lamp green and control switch 8008,4 pole	Open Product RFQ Page
8064/21-330-	8064/21-330- 30-163 (Micro Limit Switch type 8064 ATEX Certificate: PTB 02 ATEX 1031 X Connecting cable, H05VV-F, 0.75 mm2 Cable length 3m Plastic rol	Open Product RFQ Page
8070/1-1-HH-K	8070/1-1-HH-K Positionsschalter	Open Product RFQ Page
8070/1-1-HR311	8070/1-1-HR311 Positionsschalter	Open Product RFQ Page
8070/1-1-S	8070/1-1-S Positionsschalter explosionsgeschützt	Open Product RFQ Page
8102/21-31	8102/21-31 Junction box Ex	Open Product RFQ Page
8102/22-31	8102/22-31 Junction Boxes Series 8102	Open Product RFQ Page
8118/121-805	8118/121-805 / 133114 Junction box Ex e explosion -protected	Open Product RFQ Page
8118/131-814	8118/131-814 (Abzweigdose Ex e explosionsgeschützt Bemessungsbetriebsspannung AC: 750 V, Klemmbereich: 10 mm2, Gehäusematerial: Polyesterharz glasfase	Open Product RFQ Page
8118/222	8118/222 Junction Boxes	Open Product RFQ Page
8125/5051-2	8125/5051-2 STATION: CONTROL START/STOP WITH START PUSH BUTTON (GREEN COLOR) WITH EMERGENCY STOP PUSH BUTTON (RED COLOR) WITH TWO INDICATING LAMPS EXP	Open Product RFQ Page
8146/.081	8146/.081 Increased Safety Exe Dual Certified ATEX / IECEx. SIZE: 360mm x 360mm x 91mm. MAX QTY OF ENTRIES PER FACE: 1xM20x1.5 & 1xM32x1.5. Tapped Ent	Open Product RFQ Page

Part Number	Product Description	Live RFQ Link
8146/1051	8146/1051	Open Product RFQ Page
8146/1S71	8146/1S71	Open Product RFQ Page
8146/1S71-3D-1TS35+32U-	8146/1S71-3D-1TS35+32U- N 32 terminal Box EEx e, T5, C side M20x1.5 6 pcs. / D M25h1,5 1pc. M20x1.5 2 pcs.	Open Product RFQ Page
8146/2073	8146/2073 8146/2073 terminal box Ex i MaterialNr.: 8146259110	Open Product RFQ Page
8146/5073	8146/5073 -special switch Ex II 2G Ex de IIC T6 containing : -1 8544/1-31 switch 3 pole 690V, 63A -1 black turn knob, 0/OFF – I/ON -1 external earth 1	Open Product RFQ Page
8146/5-602-5002	8146/5-602-5002 disconnect	Open Product RFQ Page
8161/5-M20-13	8161/5-M20-13 Cable gland M20x1.5 Eexe	Open Product RFQ Page
8161/5-■25-17	8161/5-■25-17	Open Product RFQ Page
8161/5-■40-28	8161/5-■40-28	Open Product RFQ Page
8161/5-■50-35	8161/5-■50-35	Open Product RFQ Page
8163/1-20-E1FW-M20	8163/1-20-E1FW-M20 CABLE	Open Product RFQ Page
8415/24-A-9	8415/24-A-9 (OBSOLETE REPLACED BY 8013/321-AL) INDICATOR-AMBER/24V DC	Open Product RFQ Page
8415/24-G-9	8415/24-G-9 (OBSOLETE REPLACED BY 8013/321-AL) INDICATOR- GREEN/24V DC	Open Product RFQ Page
8415/24-R-9	8415/24-R-9 (OBSOLETE REPLACED BY 8013/321-AL) INDICATOR- RED/24V DC	Open Product RFQ Page
8415/24-W-9	8415/24-W-9 (OBSOLETE REPLACED BY 8013/321-AL) INDICATOR-WHITE/24V DC	Open Product RFQ Page
8491/11-230	8491/11-230 Original Spare Part	Open Product RFQ Page
8493/11-21-6	8493/11-21-6 Original Spare Part	Open Product RFQ Page
8537/2-703-7000	8537/2-703-7000 SAFETY SWITCH/ 25 A, 3-POLE	Open Product RFQ Page
8560/51-■4061	8560/51-■4061 (5 pcs fuse M 0,100A 250V)	Open Product RFQ Page
8560/51-4222	8560/51-4222 (Box= 5 pcs.) Klein-Sicherungselement	Open Product RFQ Page
8562/52-5030-060	8562/52-5030-060 Leitungsschutzschalter	Open Product RFQ Page
8570/11-306	8570/11-306 Schaltersteckdose	Open Product RFQ Page
8570/11-406	8570/11-406 (Schaltersteckdose explosionsgeschützt)	Open Product RFQ Page
8570/11-506	8570/11-506 Schaltersteckdose explosionsgeschützt	Open Product RFQ Page
8570/12-306	8570/12-306 PLUG 2P+PE 16A 200-250V, 60+60HZ, 6H, BLUE 16 A Plug, explosion protected Nominal voltage: 200 V ... 250 V Frequency: 50 / 60 Hz No. of po	Open Product RFQ Page
8570/12-406	8570/12-406 (Stecker explosionsgeschützt Typ : 8570/12-406 Bemessungsbetr.spg. / Frequenz: 380-415 V 50/60 Hz Bemessungsbetriebsstrom : 16 A Detaillie	Open Product RFQ Page
8571	8571 / 11- 5 drei phase Steckdose, 380 V, 32 A, Exproof	Open Product RFQ Page

Part Number	Product Description	Live RFQ Link
8571/12-5	8571/12-5 drei phase stecker, 380 V, 32 A, Exproof	Open Product RFQ Page
8575/12-100	8575/12-100 (Stecker explosionsgeschützt Bemessungsbetr.spg. / Frequenz: 20 ... 25 V 50/60 Hz Bemessungsbetriebsstrom : 16 A Detaillierte Polzahl : 2	Open Product RFQ Page
8602	8602 STOP (Button label Label marking : STOP Colour of label : red For further information, see : www.r-stahl.com Web code 8082A)	Open Product RFQ Page
8602/3	8602/3 Pushbutton	Open Product RFQ Page
8602A0726-1-3-rr-V	8602A0726-1-3-rr-V Original Spare Part	Open Product RFQ Page
8602A0727	8602A0727 1-2-R-V (Rotary handle, small lockable explosion-protected Enclosure material : Polyamide Seal : Standard Mounting : with threaded Switching	Open Product RFQ Page
8703-PUSH	8703-PUSH BUTTON ASSEMBLY PUSH BUTTON FOR STOP-NO CONTACT	Open Product RFQ Page
9001/00-280-100-101	9001/00-280-100-101 Max. Voltage Uo : 28 V Max. Current Io : 100 mA Max. Demand Po : 700 mW Number of channels : 1 Polarity : negative polarity Applic	Open Product RFQ Page
9001/01-168-020-101	9001/01-168-020-101 (158555) Single-channel safety barriers explosion-protected	Open Product RFQ Page
9001/01-168-075-101	9001/01-168-075-101	Open Product RFQ Page
9001/01-280-075-101	9001/01-280-075-101	Open Product RFQ Page
9002/22-032-300-111	9002/22-032-300-111 R.STAHL Safety barrier	Open Product RFQ Page
9118/11-11-10	9118/11-11-10 - OBSOLETE (REPLACED BY 9118/11-11-10) ics modul-mA isolating repeater(max vol.:8.7 V max. cur.:0.4 mA max. pow.:11mW power supp.:24 vDC	Open Product RFQ Page
9160/13-11-11S	9160/13-11-11S (ISpac Isolating Repeater Transmitter Supply Unit Field Circuit Ex i explosion-protected Max. Voltage Uo : 27 V Max. Current Io : 88 mA	Open Product RFQ Page
9164/13-22-08	9164/13-22-08 (ISpac mA-Trennübertrager Feldstromkreis Ex i explosionsgeschützt Max. Spannung Ui: 30 V, Max. Strom li: 150 mA, Max. Leistung Pi: 800 m	Open Product RFQ Page
9165/16-11-10S	9165/16-11-10S (ISpac Isolating Repeater Field Circuit Ex i explosion-protected Max. Voltage Uo : 25,6 V Max. Current Io : 96 mA Max. Demand Po : 605	Open Product RFQ Page
9165/16-11-11s	9165/16-11-11s Trennübertrager	Open Product RFQ Page
9170/10-11-11S	9170/10-11-11S (ISpac Isolating Repeater Switching Repeater Field Circuit Ex i explosion-protected Max. Voltage Uo : 10,6 V Max. Current Io : 24 mA Ma	Open Product RFQ Page
9170/10-12-21s	9170/10-12-21s (ISpac Switching amplifier Field Circuit Ex i explosion-protected Type : 9170/10-12-21s Max. Voltage Uo : 10,6 V Max. Current Io : 24 m	Open Product RFQ Page
9170/20-12-11S	9170/20-12-11S 160293, IS PAC Isolating Repeater Switching Repeater Field Circuit Ex i explosion-protected Type : 9170/20-12-11s Max. Voltage Uo : 10,	Open Product RFQ Page

Part Number	Product Description	Live RFQ Link
9175/20-16-11S	9175/20-16-11S (ISpac Isolating Repeater Binary Output explosion-protected Max. Voltage Uo : 27,6 V Max. Demand Po : 760 mW Max. Current Io (Ex ia) :	Open Product RFQ Page
9176/20-12-00S	9176/20-12-00S (Binary output loop-powered IS pac)	Open Product RFQ Page
9182/10-51-11S	9182/10-51-11S (ISpac Isolating Repeater Temperature Transmitter Field Circuit Ex i explosion-protected Max. Voltage Uo : 6,5 V Max. Current Io : 19,7	Open Product RFQ Page
9185/11-35-10	9185/11-35-10 FIELDBUS ISOLATING REPEATER	Open Product RFQ Page
9194/50-01	9194/50-01 (ISpac pac-Bus single element explosion-protected Nominal voltage : 24 V DC Min. ambient temperature : -20 °C Max. ambient temperature : +7	Open Product RFQ Page
9440-15-01-11	9440-15-01-11 CPU&POWER 0000-9626-48	Open Product RFQ Page
9460/12-08-11	9460/12-08-11 I.S.1 8AI MODULE	Open Product RFQ Page
9465/12-08-11	9465/12-08-11	Open Product RFQ Page
9466/12-08-11	9466/12-08-11 ANALOG OUTPUT MODULE (NOV P/N:0000-9626-44)	Open Product RFQ Page
9470/22-16-11	9470/22-16-11	Open Product RFQ Page
9475/12-08-61	9475/12-08-61 DIGITAL OUTPUT MODULE (NOV P/N:0000-9626-46)	Open Product RFQ Page
9475/22-08-51	9475/22-08-51 I.S.1 8DO MODULE	Open Product RFQ Page
9480/12-08-11	9480/12-08-11 ANALOG INPUT MODULE (NOV P/N:0000-9626-45)	Open Product RFQ Page
9575/12-08-61	9575/12-08-61	Open Product RFQ Page
Art.	Art. Nr. 150495 , type 8570/12-506 Stecker explosionsgeschützt	Open Product RFQ Page
ART.NR.321000	ART.NR.321000 INTERIOR REPAIR KIT COMPLETE	Open Product RFQ Page
ART.NR.331021	ART.NR.331021 button	Open Product RFQ Page
B/2	B/2 F11/101.211 650/2550 KW 0.06/0.025 AMPER 0.7/0.9 Original Spare Part	Open Product RFQ Page
Box	Box EEx e, T5, C side M20x1.5 6 pcs. / D M25h1,5 1pc. M20x1.5 2 pcs. Original Spare Part	Open Product RFQ Page
C-LUX	C-LUX 6108 VB Original Spare Part	Open Product RFQ Page
D40S5-23AGV	D40S5-23AGV lock pin ,cross recessed , VZ CrVI- free, clamping range 18-18,8mm	Open Product RFQ Page
EXLUX	EXLUX 6008 VB Original Spare Part	Open Product RFQ Page
HF-7200	HF-7200 Original Spare Part	Open Product RFQ Page
Membrane	Membrane / Sticker "PUSH" Original Spare Part	Open Product RFQ Page
PART	PART NO: PTB01 ATEX 1129 SWITCH,CONTROL,MOTOR	Open Product RFQ Page
PUSH	PUSH BUTTON CONTROL BOX 1739084219 Original Spare Part	Open Product RFQ Page

Part Number	Product Description	Live RFQ Link
ST	ST 37-2K DIN ISO 2338 5m6x16,L 30x4x73	Open Product RFQ Page
Steuergerät	Steuergerät Auswahl STH 6102-009 Original Spare Part	Open Product RFQ Page
SVM	SVM 280 cartridge systems	Open Product RFQ Page
TEX	TEX 303016-S1 Original Spare Part	Open Product RFQ Page

Axiparts Offices

Germany Head Office: Lise-Meitner-Straße 13, 89081 Ulm, Germany

USA Office: 16225 Park Ten Pl #500, Houston, TX 77084, United States

Dubai Office: HDS Business Centre Tower, Cluster M, 33rd Floor, Jumeirah Lake Towers, Dubai, United Arab Emirates